

## APPLICATION

Enhanced performance cable for transmission of high speed data, digital and analogue voice and video (RGB) signals on LANs. Supports Gigabit Ethernet (100 baseT) standard. Operates at bandwidth up to 100MHz.

**This cable well exceeds the requirements of ANSI/TIA-568-C.2 and ISO/IEC 11801**

Approval : UL Listed E257005  & ETL - UL Verified to ANSI/TIA-568-C.2

## CONSTRUCTION

**Conductor** : 24 AWG Solid bare Copper

**Insulation** : High Density Polyethylene

**Pairs** : 2 Insulated conductors  
twisted together


**Sheath** : PVC

**Cable Diameter** : 5.0±0.2 mm

**Printing** : Each meter printed with  
**STERLITE CATEGORY 5e ANSI/TIA-568-C.2 4/24 AWG UTP MONTH/ YEAR XXX M**

**OR**

As per Customer Request



## COLOUR CODE

<u>PAIR NO</u>	<u>COLOUR</u>
1-2	White-Orange Stripe and Orange
3-6	White-Green Stripe and Green
4-5	White-Blue Stripe and Blue
7-8	White-Brown Stripe and Brown

## ELECTRICAL PROPERTIES

Characteristics Impedance	: 100 ± 15 Ohms
Conductor Resistance	: ≤ 9.38 Ω/100m
Mutual Capacitance	: < 5.6nF/100m
Resistance Unbalance	: 5% Max
Capacitance Unbalance	: 330pF/100m
Delay Skew	: < 45nS

Issued Date : 07.07.2019

Approved and Issued By

Head Technical

Page 1 of 2

## CONTACT

Works: Survey No. 33/1/1, Waghdhara Road, Dadra Union Territory of Dadra & Nagar Haveli Silvassa-396230 INDIA

Website : [www.sterlitetechnologies.com](http://www.sterlitetechnologies.com)



## TRANSMISSION CHARACTERISTICS PER 100M

Frequency MHz	Insertion Loss (dB/100m)	RL (dB)	NEXT (dB)	PSNEXT (dB)	ELFEXT (dB)	PSELFEXT (dB)	ACR (dB)	PSACR (dB)
1	2.0	20.0	65.3	62.3	63.8	60.8	63.3	60.3
4	4.1	23.0	56.3	53.3	51.8	48.8	52.2	49.2
8	5.8	24.5	51.8	48.8	45.7	42.7	46.0	43.0
10	6.5	25.0	50.3	47.3	43.8	40.8	43.8	40.8
16	8.2	25.0	47.2	44.2	39.7	36.7	39.0	36.0
20	9.3	25.0	45.8	42.8	37.8	34.8	36.5	33.5
25	10.4	24.2	44.3	41.3	35.8	32.8	33.9	30.9
31.25	11.7	23.6	42.9	39.9	33.9	30.9	31.2	28.2
62.5	17.0	21.5	38.4	35.4	27.9	24.9	21.4	18.4
100	22.0	20.1	35.3	32.3	23.8	20.8	13.3	10.3

## MECHANICAL PROPERTIES

<b>Bending Radius</b>	: < 4 X Cable Dia (mm) at -20°C ± 1°C
<b>Pulling Force</b>	: 100 N
<b>Temperature Range</b>	
Installation	: 0° to + 50°C
Operation	: -20° to +70°C

## AVAILABLE COLORS

Grey – RAL 7037 , RAL 7035

Blue – RAL 5017, RAL 5012

## CONNECTION SYSTEM

Compatible with all common systems according to ANSI/TIA-568-C.2 & ISO/IEC 11801

## FLAME PROPERTIES

Flammability Test – IEC 60332-1

## PACKING

Available in easy-pull boxes of guaranteed 305m Length  
OR As per Customer's Request

Issued Date : 07.07.2019

Approved and Issued By

Head Technical

Page 2 of 2

## CONTACT

Works: Survey No. 33/1/1, Waghdhara Road, Dadra Union Territory of Dadra & Nagar Haveli Silvassa-396230 INDIA

Website : [www.sterlitetechnologies.com](http://www.sterlitetechnologies.com)